

## Rust Resistant Film (CVC1)

Ferrous metals require protection from rust and corrosion. Rust resistant CVC1 prevents the corrosion of ferrous metals, without the need for costly coatings. CVC1 will not alter the electrical or mechanical properties of the bagged product.

Genuine Autobag® bags-on-a-roll and SidePouch® bags-in-a-box are system-matched and guaranteed to run on all Automated Packaging Systems' bagging equipment.

## Technical Information

Compliances	N/A
Press Printing	Yes
Imprinting	Yes
Trim Seal	No
Mil Thickness	2.0, 3.0
Configuration	Autobag; SidePouch with restrictions

Performance Data:	U/M	2.0/SD	3.0/ET	ASTM
Haze	%	13.1	16.8	D-1003
Puncture Resistance (Dart)	grams	129	169	D-1709
Tensile Strength MD	psi	2770	2630	D-882A
Tensile Strength TD	psi	2450	2300	D-882A
Elongation MD	%	320	340	D-882A
Elongation TD	%	580	580	D-882A
Elmendorf Tear MD	grams	310	371	D-1922
Elmendorf Tear TD	grams	272	414	D-1922
OTR	cc/100in <sup>2</sup> /day	300	180	D-3985
MVTR	g/100in <sup>2</sup> /day	0.796	0.57	F-1249

## Formulation

### • CVC1



## Features & Benefits

- Integrated corrosion inhibitors
- Does not alter product characteristics
- Flexible options and features



Chart reflects nominal test data values. Actual results may fluctuate due to inherent process variation. Test data and mil thickness reflect CVC1 material only. Certain minimum purchase volumes may apply.