





	BAGGER SPECIFICATIONS				
	WEIGHT	350 LBS (158.6 KG)			
B	ELECTRICAL	UNIVERSAL INPUT, 100V TO 240V VAC, 50/60 Hz Power consumption: 500W (VA) MAX			
	AIR FEED	5 CFM/80 PSI OF CLEAN, DRY AIR			
	PASS-THROUGH	UP TO 5 INCHES (127 MM)			
	BAG THICKNESS	I.09 - 4.0 MIL			
	BAG SIZES	WIDTH: 2 to 12 INCHES (51 TO 305 MM) / LENGTH: 3 to 20 INCHES (76 TO 508 MM)			
	WEIGHT CAPACITY	UP TO 5 LBS (WITH LOAD SHELF)			
		PRINTER SPECIFICATIONS			

WEIGHT
ELECTRIC AIR FEED
AIR FEED
LABEL SI

— 67.0 (|70|.8 MM) —

			В	DMF	7 -   - 2	3265	UPDATED POWER CONSUMPTION: 500W WAS I500W, 300W WAS 2.4kW		
	<b></b>		A	DMF	- 5-20	2895	RELEASED		
	FINISH	NONE	R E V	ΒY	DATE	ECN	DESCRIPTION		
	MATERIAL	NONE							
	UNLESS OTH	RFACES TO BE NO GREATER THAN 125 [3,2] 🗸 RWISE NOTED BE FREE OF BURRS AND SHARP EDGES					omated		
0	TOLERANCE     INCHES     mm       I PLACE DIMS     ±     .1     ±2,5       2 PLACE DIMS     ±     .02     ±0,51       3 PLACE DIMS     ±     .02     ±0,10       ANGULAR     ±     1/2°   NOTICE: THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND IT SHALL NOT BE USED OR REPRODUCED OR ITS CONTENT DISCLOSED, IN WHOLE OR PART, WITHOUT THE PRIOR WRITTEN CONSENT OF AUTOMATED PACKAGING SYSTEMS INC.		INTEL PACKAGING SYSTEMS						
Vaulte			DRAWING S	SIZE	SCALE	DRAWN B	Y BOM REFERENCE NUMBER		
			E		/4	NAME: DMF DATE: II-I2	2-20		
	INCH [MM] THIRD ANGLE PROJECTION		F ()	OTPR	INT, A	B500	DRAWING NO. SHEET 1 OF 1 REV		
			& ALSOOP W/UNWIND FP273 B						

PRINTER SPECIFICATIONS				
	66 LBS (30 KG)			
ICAL	100-240V VAC, 50/60 Hz, 300W			
e d	SUPPLIED FROM BAGGER			
SIZE	UP TO 4 INCHES (IO2 MM) WIDE, 20 INCHES (508 MM) LONG			